

4

3

2

1

D

D

C


C

B

B


A

A



DETAIL Z
SCALE 2:1

820-03-458-KIT
2017 Grip Rebound Piston Assy, Short Travel



SEE DETAIL Z

229-10-271
Shaft, 10mm Damper, Hard Ano, Grip, 32 27.5

820-03-525-KIT
2019 Grip, All, Bearing Housing Assy

APPLY BLUE MARINE GREASE
TO THREADS ON ALUMINUM
REBOUND NEEDLES ONLY

210-22-958
Damping Adj Part: Base Stud, M8, Grip

029-08-022
Seals: O-Ring [8.0MM ID x 1.0MM CS]
Metric, N-70, Static

TORQUE:
40±5in-lb


LOCTITE:
RED 263, 2-3 DROPS
360° COVERAGE *

010-01-012
Ball [Ø.1094]

039-00-243
Spring: Detent [.138 TLG, .087 OD, 48 lb/in]

210-03-231
Damping Adj Part: Needle, Rbd, Injection Molded, 32 27.5

029-03-005
O-Ring (-005) [.070 C.S. X 0.101 ID]



SECTION A-A

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX **FOX Factory, Inc.** Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
2019 32 27.5 80-120
Grip Damper Shaft Assy

SIZE DWG. NO.
C **820-03-581-KIT**

PLOT SCALE 1:1 SHEET 1 OF 1

ProE ASSEM