



REBOUND METERING RODS:
 210-84-017: Damp Adj Part: (T) FLOAT 2017, Metering Rod, Rebound [110 ID X 3.121 TLG], 55mm, 9mm Thru Shaft (EX130)
 210-84-018: Damp Adj Part: (T) FLOAT 2017, Metering Rod, Rebound [110 ID X 3.515 TLG], 65mm, 9mm Thru Shaft (Remedy/Slash)

SHAFTS:
 229-19-330: Shaft: Main, Chrome Plated Steel, 9mm thru shaft, 50/55mm, 3.018 TLG (EX130)
 229-19-331: Shaft: Main, Chrome Plated Steel, 9mm thru shaft, 60/65mm, 3.412 TLG (Remedy/Slash)

COMPRESSION RODS:
 210-22-832: Inner Comp Rod, Trek RG, 3.580 TLG, 1.875/2.00 DRCV, 2.125/2.25 Trunnion (EX130)
 210-22-839: Inner Comp Rod, 9mm Thru Shaft, 230 x 60/65, 3.975 TLG (Remedy/Slash)

812-06-087-KIT
 Bearing Assy: FLOAT, 2018, Short [.940 Bore, 1.500 Bore, 9mm Shaft]

SLAVE SHAFTS:
 229-19-310: Shaft: Slave, 9mm thru shaft, Reaktiv, 50/55mm, 3.072 TLG (EX130)
 229-19-311: Shaft: Slave, 9mm thru shaft, Reaktiv, 60/65mm, 3.466 TLG (Remedy/Slash)

BODY ASSEMBLIES:
 806-61-225-KIT: Body Assembly: 9mm Thru Shaft, [.940 Bore], 210 x 50/55, Black Ano (EX130)
 806-61-228-KIT: Body Assembly: 9mm Thru Shaft, [.940 Bore], 230 x 60/65, Kashima (Remedy/Slash)

AIR SLEEVE ASSEMBLIES:
 806-29-765-KIT: Sleeve Assembly: 2020 Float Evol LV, Ano, 210 x 50/55, 9mm Thru Shaft
 806-29-767-KIT: Sleeve Assembly: 2020 Float Evol LV, Kashima, 210 x 50/55, 9mm Thru Shaft
 806-29-766-KIT: Sleeve Assembly: 2020 Float Evol LV, Ano, 230 x 60/65, 9mm Thru Shaft
 806-29-768-KIT: Sleeve Assembly: 2020 Float Evol LV, Kashima, 230 x 60/65, 9mm Thru Shaft

805-00-117-KIT
 Piston Assembly: Floating, With Bleed, [Ø 0.625 Bore], 9mm Thru Shaft

808-17-401-KIT
 Eyelet Assy: 2020, Trek 9mm Thru Shaft, Reaktiv, LV, Trunnion

VOLUME SPACERS:
 233-00-351: Volume Spacer: 2018 Float DPS 0.4in³ Plastic, Green (EX130)
 233-00-352: Volume Spacer: 2018 Float DPS 0.6in³ Plastic, Yellow (Remedy/Slash)

233-00-260
 Spacer: Metric Travel [.360 ID X .550 OD X 2.5mm TLG] 6061, Black Ano (Remedy/Slash)

233-00-261
 Spacer: Metric Travel [.360 ID X .550 OD X 5.0mm TLG] 6061, Black Ano (Remedy/Slash)

GREASE:
 THIN LAYER
 SLICK HONEY

813-00-275-KIT
 Rezi End Cap Assy: 9mm Thru shaft

038-00-173
 Retaining Ring: Wire [.600 OD X .040 CS] 17-7 SST

GREASE:
 THIN LAYER
 SLICK HONEY

GREASE:
 THIN LAYER
 SLICK HONEY

GREASE:
 THIN LAYER
 SLICK HONEY

TORQUE:
 10-15 IN-LB

LOCTITE:
 RED 277
 1-3 THREADS 180°

TORQUE:
 85±5 IN LB

TORQUE:
 60±5 IN LB

TORQUE:
 22±5 IN LB

TORQUE:
 15±2 FT LB

TORQUE:
 45±5 IN LB

GREASE:
 THIN LAYER
 SLICK HONEY

213-01-702
 Clevis: Lower Trunnion, 9mm Thru Shaft

029-03-022
 O-Ring (-022) [.070 C.S. X .989 ID]

038-00-174
 Retaining Ring: External, DIN 471, 9mm shaft

812-06-087-KIT
 Bearing Assy: FLOAT, 2018, Short [.940 Bore, 1.500 Bore, 9mm Shaft]

010-01-000
 Ball [Ø 0.1250] Steel

SECTION B-B
 018-01-034
 Set Screw [#8-32 X 0.125 TLG] Flat Point, SS

029-08-060
 Seals: O-Ring [6.0mm ID x 1.5mm CS] Metric, N-70, Static

029-05-030
 Seals: O-ring [.050 C.S. x .154 ID] Special N0552-90, Dynamic

029-12-000
 Seals: O-ring, Square cut [0.087 ID X 0.039 WALL X 0.036 TH], NA103-70, Dynamic

010-01-009
 Ball [Dia 1.5MM] Steel

029-08-122
 Seals: O-Ring [8.5mm ID x 2.5mm CS] Metric, N-70, static

043-15-010
 Valve: [1.100 OD X .356 ID x .015 TH]