

4

3

2

1

820-05-623-KIT
2020 Grip 34, 36 & 38 P-S Topcap Interface Parts

Spring: Wave, 4 Turns, [1.562 Bpre, .375 Shaft, .260 Height, 37.0 lb/in] SS

Damping Adj Part: Detent, Molded, Grip

Damping Adj Part: Detent, Molded, Grip

Seals: U-Cip, Shore 70A, 2013 CTD-ADJ, Remote O/C-CTD

TORQUE:
4±1 in-lb

GREASE:
THIN LAYER
OF SLICK HONEY

GREASE:
LIBERALLY WITH
SLICK HONEY

ENGAGE 2X FEATURES

SECTION A-A
SCALE 2.500

820-05-328-KIT
2017 34 27.5 and 29in Grip Bottom Stud Interface Parts

241-01-011
Fastener, Custom: Crush Washer, Plastic, 13mm

241-00-011
Fastener, Custom: Nut, Bottom, R

REBOUND KNOB

TORQUE:
5.0±0.5 IN.LB.

LOCTITE:
BLUE 242 OR 243
ONE DROP

TORQUE:
150±7
(IN-LB)

SCREW

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

FOX **FOX Factory, Inc.** Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
**2021 34 GRIP CARTRIDGE
ASSEMBLIES COMPLETE**

SIZE DWG. NO.

C

PLOT SCALE 0.75:1

SHEET 1 OF 2

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

ProE ASSEM