

4

3

2

1

029-03-024-A
O-RING

TOPCAP

060-00-018
Pin: Dowel [Ø 0.125 X 0.250 TLG]

! IMPORTANT:
ALIGN PIN WITH
BLIND HOLE IN TOPCAP

FLOW DIVIDER

029-08-004
Seals: O-Ring [3.0MM ID x 1.0MM CSI Metric, N-70, Static

GREASE:
THIN LAYER
OF SLICK HONEY

TORQUE:
75±5 IN. LB.

GREASE:
SLICK HONEY

210-22-594
Flow Plate, 2013 CTD, F/P

210-22-595
Hard Stop Plate, 2013 CTD

TORQUE:
11±3 IN. LB.


GREASE:
THIN LAYER
OF SLICK HONEY

060-00-019

Pin: Dowel [Ø 0.078 X 0.188 TLG]

210-22-762
Compression Adjuster Rod, 2014 FIT CTD

019-01-023
Fastener, Standard (Metric): Hexagon Socket, Flanged Button Hd Cap Screw, M3 X 8mm



SECTION A-A

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX Factory, Inc. Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
**2015 34 P-S FIT CTD
Topcap Assy**

SIZE DWG. NO.

C

PLOT SCALE 2.00:1

SHEET 1 OF 1

4

3

2

ProE ASSEM