



Seals: O-Ring [16.5mm ID X 1.5mm CS] Metric, N-70, Static

039-00-205
Spring, Comp. Check

044-06-060
Valve: [.600 X .252 X .006]

GREASE:
THIN LAYER
OF SLICK HONEY

040-20-066
Valve: [0.660 OD X 0.377 ID X 0.020 TH]

210-22-877
Reflow Cap, FIT 4

OIL:
THIN LAYER OF FOX R3 DAMPER OIL

IMPORTANT:
NOTE ORIENTATION
OF SPRING

210-22-887
Bladder Seal Ring Lower, FIT4

TORQUE:
55±5 IN.LB.

210-22-303
Bladder, 010 RL_RLC

038-00-063
RING: INTERNAL SMALLLEY (VH-100-S02)

GREASE:
THIN LAYER
OF SLICK HONEY

210-22-997
Compression Piston Clamp, FIT4

GREASE:
THIN LAYER
OF SLICK HONEY

210-22-996
Shaft: Coupler, 0.375" OD X 0.254" ID, 7075-T6, FIT4

029-03-020
O-Ring (-020) [.070 C.S. X .864 ID]

210-22-886
Bladder Seal Ring Upper, FIT4

TORQUE:
75±5 IN.LB.
COMPRESSION CLAMP INTO TOPCAP ONLY

820-03-544-KIT
2018 FIT4 F-S Compression Valving Assy, E18

TORQUE:
55±5 IN.LB.

036-01-093
Seals: U-cup, Low Friction, 9mm Shaft

029-03-024-A
Seals: O-Ring [(-024) .070 C.S. X 1.114 ID] Standard, N-70, Static

Body, Topcap, 34, FIT4 Remote, U-Cup

TOPCAP PARTS:
820-03-537-KIT: 2018 FIT4 F-S Top Cap Parts, Remote, U-Cup, Push-Lock
820-03-540-KIT: 2018 FIT4 F-S Top Cap Parts, Remote, U-Cup, Push-Unlock
820-03-532-KIT: 2018 FIT4 F-S Top Cap Parts, Remote, U-Cup

FOX Factory, Inc.
130 Hangar Way, Watsonville, CA 95076 USA
Ph 831-768-1100
Fax 831-768-9312

2019 34 F-S FIT4
Remote Topcap Assemblies

SIZE DWG. NO.
C

PLOT SCALE | .00:1 |

SHEET | OF |

PROPRIETARY - THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.