


4

3

2

1



DETAIL Y

- 019-02-025 Fastener, Standard (Metric), Nut, M6 x .75
- 241-02-106 Fastener, Custom: Bolt Piston Comp Grip
- 039-00-349 Spring: [0.200 TLG X .400 ID X 0.50 lbs/in] Stainless Steel
- 045-00-151 Valve: Metric [8.00mm OD X 5.55mm ID X 0.25mm THK] Custom, Check
- 222-01-295 Piston Damping Comp 20.0 Bore
- 029-08-196 Seals: O-Ring [16.0mm ID X 2.0mm CS] Metric, N-70, Dynamic
- 029-03-011 O-Ring (-011) [.070 C.S. X .301 ID]
- 223-00-049 Piston Floating: IFP, Grip
- 029-08-188 O-Ring [17mm ID X 1.5mm CS], N-90, Static
- 820-03-331-KIT 2017 Grip Compression Valving
- 029-08-084 Seals: O-Ring [8mm ID X 1.5mm CS] Metric, N-70, Static
- 210-22-957 Damping Adj Part: Hat Preload Comp




029-08-108
Seals: O-Ring [4.0mm ID x 1.5mm CS] Metric, N-70, Static

- 231-00-026 Sleeve: Isolator, Spring, OD, Grip
- 019-01-116 Fastener Standard (Metric): PIN SS 2 X 12

Shaft, Damper, Comp, 8mm, Grip

210-22-956
Damping Adj Part: Needle, Comp, Grip





039-00-378
Spring, Piston, Floating, Grip 160

231-00-025
Sleeve: Isolator, Spring, ID, Grip

029-03-024-A
Seals: O-Ring [(-024) .070 C.S. X 1.114 ID] Standard, N-70, Static

Damping Adj Part: Topcap 34 2018 Grip, Black Ano



SEE DETAIL Z

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX Factory, Inc. Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE **2019 34 Grip Damper, Topcap Assy**

SIZE DWG. NO. **C 820-05-519-KIT**

PLOT SCALE 0.80:1 SHEET 1 OF 1

4

3

2

1