

038-00-118  
Retaining Ring: Internal, Smalley HHM-34-S02, Hoopster, 302 SS

241-00-005-A  
Fastener, Custom: Nut, Bottom, R\_RL\_RLC

241-01-002-C  
Fastener, Custom: Crush Washer, Plastic, R\_RL\_RLC

IMPORTANT:  
ENSURE RETAINING RING IS FULLY  
INSERTED INTO GROOVE FULL 360°

TORQUE:  
50±5 IN.LB.

OIL:  
10cc Gold 20wt. Oil  
025-03-010

Air Shaft Assy  
(SEE TABLE)

Topcap Assy  
(SEE TABLE)

Torx T8 Screw  
241-02-093

GREASE:  
THIN LAYER  
OF SLICK HONEY

029-08-088  
O-Ring

TORQUE:  
220±5 IN.LB.

029-03-008  
O-Ring (-008) [ .070 C.S. X .176 ID]

234-04-550  
(T) Spring Hardware: 2014 36 FLOAT Air Topcap, Al, Blue Ano

DESCRIPTION	Topcap Assembly	Transfer Hole	Air Shaft Assembly	234-04-627 Spacer Quantity
Air Spring Assy, 36 180, FLOAT NA	820-05-304-KIT	#1	820-02-319-KIT	0
Air Spring Assy, 36 170, FLOAT NA	820-05-305-KIT	#2	820-02-324-KIT	1
Air Spring Assy, 36 160, FLOAT NA	820-05-304-KIT	#1	820-02-321-KIT	0
Air Spring Assy, 36 150, FLOAT NA	820-05-305-KIT	#2	820-02-322-KIT	1
Air Spring Assy, 36 140, FLOAT NA	820-05-306-KIT	#3	820-02-323-KIT	2

**FOX** FOX Factory, Inc. Ph 831-768-1100  
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE  
**2015 36 140-180mm  
FLOAT NA Air Spring Assys**

SIZE DWG. NO.  
**C**  
PLOT SCALE | .00:1 | SHEET | OF |

- PROPRIETARY -  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.