



241-00-020  
Fastener, Custom: Cover, Nut 011 RC2

REFERENCE ONLY  
(FOR INSTALLATION  
INTO FORK)

TORQUE:  
65±5 IN-LB

241-00-022  
Fastener, Custom: Nut, Bottom, 011 RC2

241-01-011  
Fastener, Custom: Crush Washer, Plastic, 13mm

TORQUE:  
5.0±0.5 IN-LB

LOCTITE:  
BLUE 242  
ONE DROP

018-01-004-A  
Fastener, Standard: Screw [#8-32 X 0.250 TLG]

210-03-120  
Knob, Rebound, 2011 36-40

029-08-053  
Seals: O-Ring [15mm ID x 1.5mm CS] Metric, N-70, Static

820-05-377-KIT  
2016 FIT4 Bottom Stud Interface Parts, RC

REFERENCE ONLY  
(FOR INSTALLATION  
INTO FORK)

TORQUE:  
220±5 IN-LB

GREASE:  
THIN LAYER  
BLUE MARINE

TORQUE:  
11±3 IN-LB

036-01-043  
Seals: U-Cup, Shore 70A, 2013 Fit-CTD and CTD-ADJ

210-03-175  
Knob, Low Speed Compression, 2016 RC

019-01-095  
Fastener, Standard (Metric): Screw [M3 X 6mm] SHCS, Patchlock

820-05-348-KIT  
2016 FIT4 TopCap Interface Parts, RC

CARTRIDGE ASSY

**FOX** FOX Factory, Inc. Ph 831-768-1100  
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE  
**2016 36 RC  
FIT4 Cart Assy Complete**

SIZE DWG. NO.  
D

PLOT SCALE 1.00:1

SHEET 1 OF 1

PROPRIETARY  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.