



018-01-004-A
Fastener, Standard: Screw [#8-32 X 0.250 TLG]

TORQUE:
5.0±0.5 IN-LB

LOCTITE:
BLUE 242
ONE DROP

TORQUE:
50±5 IN-LB

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

210-22-446
REBOUND KNOB

820-05-335-KIT
BASE STUD INTERFACE PARTS

241-00-011
BOTTOM NUT

241-01-011
CRUSH WASHER

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

TORQUE:
220±5 IN-LB

CARTRIDGE ASSY

IMPORTANT:
NOTE U-CUP
ORIENTATION

DETAIL A
SCALE 3.000

SEE DETAIL A

IMPORTANT:
DO NOT ALLOW PULLEY
TO ROTATE WHILE TORQUING

TORQUE:
11±3 IN-LB

210-22-944
Cable Pulley, Remote, FIT4

GREASE:
THIN LAYER
BLUE MARINE

210-22-947
Damping Adjust Part: Housing, Remote, Hubless, FIT4

039-00-291
Spring: Torsion 2013 Damper CTD Remote, .048 Square Wire, 0.600 Mean Coil Diam (

002-02-050
Bearing: External [0.115 W X 0.810 OD X 0.030 TH, Ø 0.750 Bore] Turcon,Blue,Ring

036-01-044
Seals: U-Cup, Shore 70A, 2013 CTD-ADJ, Remote Fit-CTD and Remote O/C-CTD

019-01-088
Set Screw [M4x4mm], SST, Cup Point, Patchlock

019-02-024
Fastener Standard (Metric): Socket Head Cap [M6 X 1.0 X 6MM] SST, Patchlock

820-05-333-KIT
2016 FIT4 TopCap Remote Interface Parts P-S

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX Factory, Inc.
130 Hangar Way, Watsonville, CA 95076 USA
Ph 831-768-1100
Fax 831-768-9312

TITLE
**2016 P-S Remote 36mm
FIT4 Cart Assy Complete**

SIZE DWG. NO.
D

PLOT SCALE 1.00:1

SHEET 1 OF 1