

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

TORQUE:
65±5 IN-LB

TORQUE:
5.0±0.5 IN-LB

LOCTITE:
BLUE 242
ONE DROP

018-01-004-A
Fastener, Standard: Screw [#8-32 X 0.250 TLG]

210-22-446
REBOUND KNOB

820-05-335-KIT
BASE STUD INTERFACE PARTS

241-00-011
BOTTOM NUT

241-01-011
CRUSH WASHER

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

TORQUE:
220±5 IN-LB

039-00-246
Spring: Detent [.180 TLG X .090 OD X 100 lb/in] SS, LHW

234-04-779
Plate, Detent Spring Retainer, 2013 CTD Performance

038-00-136
Retaining Ring: External, 8.5mm Shaft, 302SST

GREASE:
THIN LAYER OF
BLUE MARINE ON BALL

010-01-004-A
BALL DIA .078

DETAIL A
SCALE 4.000

CARTRIDGE ASSY

SEE DETAIL A FOR PARTS

210-22-915
KNOB, COMPRESSION SELECTOR, P-S, FIT4

019-02-024
Fastener Standard (Metric): Socket Head Cap [M6 X 1.0 X 6MM] SST, Patchlock

820-05-331-KIT
2016 FIT4 TopCap Interface Parts P-S

SEE DETAIL A

FOX Factory, Inc.
130 Hangar Way, Watsonville, CA 95076 USA
Ph 831-768-1100
Fax 831-768-9312

TITLE
**2016 Performance Series
36mm FIT4 Cart Assy Complete**

SIZE DWG. NO.
D

PLOT SCALE 1.00:1

SHEET 1 OF 1

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.