



GREASE:
THIN LAYER OF SLICK HONEY
BOTH SIDES 360°

IMPORTANT:
NOTE: LOCKING TAB
ORIENTATION

GREASE:
THIN LAYER OF
SLICK HONEY

TORQUE:
180 ± 5 IN.LB.

GREASE:
THIN LAYER OF
SLICK HONEY

TORQUE:
180 ± 5 IN.LB.

TORQUE:
12 FT.LB.

GREASE:
THIN LAYER
OF SLICK HONEY

TORQUE:
180 ± 5 IN.LB.

GREASE:
THIN LAYER
OF SLICK HONEY

TORQUE:
12 FT.LB.

LOCTITE:
RED 263, 2-3 THREADS
180° COVERAGE

GREASE:
THIN LAYER
OF SLICK HONEY

GREASE:
THIN LAYER
OF SLICK HONEY

IMPORTANT:
NOTE ORIENTATION

GREASE:
THIN LAYER
OF SLICK HONEY

TORQUE:
30 ± 2 IN.LB.

SHAFT ASSY

NEGATIVE AIR SEALHEAD

043-15-010
Valve: [1.100 OD X .356 ID x .015 TH]

029-08-122
Seals: O-Ring [8.5mm ID x 2.5mm CS]Metric, N-70, static

(043-15-101)

TRAVEL AND VOLUME REDUCER

029-03-134
O-Ring (-134) [1.103 C.S. X 1.862 ID]

VOLUME REDUCER

(029-03-134)

Shaft Eyelet

Sleeve Assy

AIR SLEEVE

029-00-025
O-Ring (-025) [1.070 C.S. X 1.176 ID]

OUTER BODY

INNER TUBE

EYELET ASSY

805-00-027

Piston Asm: Floating [Ø1.070 Bore, .325 TLG]

813-00-095
Reservoir Cap Assembly: 2016 DHX2

038-01-024
Retaining Ring: Wire [1.200 OD X 0.040 CS] 17-7 SST

813-00-097
Reservoir End Cap Assembly: 2016 DHX2