

4

3

2

1

241-00-005
Fastener, Custom: Nut, Bottom, R_RL_RLC

241-01-002
Fastener, Custom: Crush Washer, Plastic, R_RL_RLC

TORQUE:
50±5 IN.LB.
(INTO FORK CHASSIS)

IMPORTANT:
INSPECT 100% THAT RETAINING RING
IS FULLY INSTALLED INTO GROOVE FULL 360°

038-00-137
RETAINING RING

029-03-008
O-Ring (-008) [.070 C.S. X .176 ID]

GREASE:
THIN LAYER
OF SLICK HONEY

820-05-347-KIT
TOPCAP ASSY

820-02-349-KIT
AIR SHAFT ASSY

TORQUE:
220±5 IN.LB.
(INTO FORK CHASSIS)

234-04-726
VOLUME SPACER

234-04-551
AIR CAP

FOX FOX Factory, Inc. Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
**Air Spring,
FLOAT NA 2**

SIZE DWG. NO.
C
PLOT SCALE | .00:1 | SHEET 1 OF 1

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

4

3

2

ProE ASSEM