

045-00-110
Valve: Metric [21.3MM OD X 13.6MM ID X 0.2MM TH]

222-01-176
Compression Bulkhead, 2011 RC2

045-00-029
Valve: Metric [16.6mm OD X 7mm ID X 0.10mm TH]

(045-00-092)

045-00-092
Valve: Metric [16.6mm OD x 7mm ID x 0.15mm TH]

045-00-070
Valve: Metric [9.6mm OD x 7mm ID x 0.25mm TH]

210-22-249
Preload Hat, 1 Piece, RC2

GREASE:
APPLY SLICK HONEY
TO THREADS

IMPORTANT:
DO NOT PINCH SHIMS
DURING ASSEMBLY

TORQUE:
75±5 IN.LB.

TORQUE:
50±5 IN.LB.

210-22-870
Bolt: Upper Compression, RC2, 0.14 in Dia Thru

210-22-405
Coupler, 2011 RC2

039-00-168
Spring, Comp Check, 011 RC2

IMPORTANT:
VERIFY 100% THAT CHECK SHIM
IS NOT PINCHED

038-01-043
Spring: Detent Wire, LSC, 2011 RC2

TORQUE:
50±5 IN.LB.

GREASE:
THIN LAYER
OF SLICK HONEY

039-00-065
Spring: Compression [0.625 TLG X 90 lbs/in] Music Wire, Ground, Gold Zinc

210-22-097
High-Speed Preloader, RC2

210-22-871
Low Speed Adjuster, RC2, 0.14 in Dia Thru

GREASE:
THIN LAYER
OF SLICK HONEY

029-08-004
Seals: O-Ring [3.0MM ID x 1.0MM CS] Metric, N-70, Static

210-10-064
LSC Coupler, 011 RC2

222-01-065
Plate, Preload, RC2

210-22-094
Adjuster Screw, High-Speed Comp, RC2

210-22-414
Upper Stud, 011 36_40 RC2

029-08-035
Seals: O-Ring [17MM ID x 1.5MM CS] Metric, N-70, Static

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

		FOX Factory, Inc.	Ph 831-768-1100
		130 Hangar Way, Watsonville, CA 95076 USA	Fax 831-768-9312
TITLE		2016 36 RC2	
		Base Valve Assembly, 831	
SIZE	DWG. NO.	820-03-483-KIT	
C			
PLOT SCALE .00:1		SHEET OF 1	