



019-01-048
Screw [M2.5 X 6mm] Socket Head Cap, Stainless

029-08-005
Seals: O-Ring [10.0MM ID x 2.0MM CS] Metric, N-70, Static

TORQUE:
5.0±1.0 IN-LBS

TORQUE:
50±5 IN LBS - REFERENCE ONLY,
FOR INSTALLATION INTO FORK

BASE STUD INTERFACE PARTS:
820-05-506-KIT: 2019 34 SC Bottom Stud Interface Parts, 29in Fork
820-05-507-KIT: 2019 34 SC Bottom Stud Interface Parts, 27.5in Fork

REBOUND KNOBS:
210-24-367: Knob: Rebound Adj, Extruded, 2019 FIT4 Lightweight, 34, 29in
210-24-375: Knob: Rebound Adj, Extruded, 2019 FIT4 Lightweight, 34, 27.5in

241-00-005
Fastener, Custom: Nut, Bottom, R_RL_RLC

241-01-002-C
Fastener, Custom: Crush Washer, Plastic, R_RL_RLC

TORQUE:
220±5 IN LBS - REFERENCE ONLY,
FOR INSTALLATION INTO FORK

SEE DETAIL A FOR PARTS

GREASE:
THIN LAYER
BLUE MARINE

TORQUE:
11±3 IN-LBS

820-05-330-KIT
2016 FIT4 TopCap Interface Parts F-S

036-01-043
Seals: U-Cup, Shore 70A, 2013 Fit-CTD and CTD-ADJ

210-22-922
Lockout Knob, F-S, FIT4

210-22-923
Compression Adjust Knob, F-S, FIT4

019-01-095
Fastener, Standard (Metric): Screw [M3 X 6mm] SHCS, Patchlock

234-04-779
Plate, Detent Spring Retainer, 2013 CTD Performance
039-00-246
Spring: Detent [1.180 TLG X .090 OD X 100 lb/in] SS, LHW
038-00-136
Retaining Ring: External, 8.5mm Shaft, 302SST

GREASE:
THIN LAYER OF
BLUE MARINE ON BALL

010-01-004-A
BALL DIA .078

DETAIL A
SCALE 4.000

IMPORTANT:
NOTE O-RING LOCATION
AT BOTTOM OF TOP CUT-OUT

SEE DETAIL A

SECTION A-A

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX Factory, Inc.
130 Hangar Way, Watsonville, CA 95076 USA
Ph 831-768-1100
Fax 831-768-9312

TITLE
**2020 34 SC 120 MAX FIT4
3 Pos Adj Cart Assy Complete**

SIZE DWG. NO.
D |

PLOT SCALE 1.00:1 | SHEET 1 OF 1