



Screw [M2.5 X 6mm] Socket Head Cap, Stainless

Seals: O-Ring [10.0MM ID x 2.0MM CS] Metric, N-70, Static

TORQUE:  
5.0±1.0 IN-LBS

TORQUE:  
50±5 IN LBS - REFERENCE ONLY,  
FOR INSTALLATION INTO FORK

**BOTTOM STUD INTERFACE PARTS:**  
820-05-228-KIT: 2017 FIT4 Bottom Stud Interface Parts, 32, SC, 29in Fork  
820-05-239-KIT: 2017 FIT4 Bottom Stud Interface Parts, 32, SC, 27.5in Fork

REBOUND KNOB

241-00-005  
Fastener, Custom: Nut, Bottom, R\_RL\_RLC

241-01-002-C  
Fastener, Custom: Crush Washer, Plastic, R\_RL\_RLC

TORQUE:  
220±5 IN LBS - REFERENCE ONLY,  
FOR INSTALLATION INTO FORK

SEE DETAIL A FOR PARTS

GREASE:  
THIN LAYER  
BLUE MARINE

TORQUE:  
11±3 IN-LBS

820-05-330-KIT  
2016 FIT4 TopCap Interface Parts F-S

Seals: U-Cup, Shore 70A, 2013 Fit-CTD and CTD-ADJ

LOCKOUT KNOB

Compression Adjust Knob, F-S, FIT4

Fastener, Standard (Metric): Screw [M3 X 6mm] SHCS, Patchlock

Plate, Detent Spring Retainer, 2013 CTD Performance

Spring: Detent [.180 TLG X .090 OD X 100 lb/in] SS, LHW

Retaining Ring: External, 8.5mm Shaft, 302SST

GREASE:  
THIN LAYER OF  
BLUE MARINE ON BALL

BALL DIA .078

DETAIL A  
SCALE 4.000

IMPORTANT:  
NOTE O-RING LOCATION  
AT BOTTOM OF TOP CUT-OUT

SEE DETAIL A

SECTION A-A

**FOX Factory, Inc.**  
130 Hangar Way, Watsonville, CA 95076 USA  
Ph 831-768-1100  
Fax 831-768-9312

TITLE  
**2021 32 SC 100 MAX FIT4 3POS ADJ  
BLACK ANO CARTRIDGE ASSEMBLIES COMPLETE**

SIZE DWG. NO.  
D |

PLOT SCALE 1.00:1 | SHEET 1 OF 1

PROPRIETARY - THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.