

4

3

2

1

D

D

C

C

B

B

A

A

241-00-005
Fastener, Custom: Nut, Bottom, R_RL_RLC

241-01-002
Fastener, Custom: Crush Washer, Plastic, R_RL_RLC

TORQUE:
50±5 IN.LB.
(INTO FORK CHASSIS)

IMPORTANT:
INSPECT 100% THAT RETAINING RING
IS FULLY INSTALLED INTO GROOVE FULL 360°

RETAINING RING

O-Ring (-008) [.070 C.S. X .176 ID]

820-05-346-KIT
Topcap Assy, FLOAT NA 2, 40, Black

820-02-581-KIT: Air Shaft Assy, 40, 203mm, FLOAT NA 2.1, +14.7cc Neg

GREASE:
THIN LAYER
OF SLICK HONEY

TORQUE:
220±5 IN.LB.
(INTO FORK CHASSIS)

234-04-726
Volume Spacer, FLOAT NA 2, 40

234-04-551
(T) Spring Hardware: 2014 40 FLOAT Air Topcap, Al, Blue Ano

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX **FOX Factory, Inc.** Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
**2021 40 FLOAT NA2
AIR SPRING ASEMBLIES**

SIZE DWG. NO.

C

PLOT SCALE | .00:1 |

| SHEET 1 OF 1

4

3

2

1

Pr oE ASSEM