

4

3

2

1

Damping Adj Part: Oil Fill Plug, 2022 FLOAT X & DHX  
210-03-330

TORQUE:  
10±2 IN.LB.

GREASE:  
THIN LAYER  
OF SLICK HONEY

Seals: O-Ring [4.0mm ID x 1.5mm CS] Metric, N-70, Static

GREASE:  
THIN LAYER  
OF SLICK HONEY

Seals: O-Ring [(-023) .070 C.S. X 1.051 ID] Standard, N-70, Static

Eyelet: 2023 DHX2 / Float X2, 6061-T6, Trunion

O-Ring (-025) [ .070 C.S. X 1.176 ID]

TORQUE:  
140±5 in-lb

GREASE:  
THIN LAYER  
OF SLICK HONEY

O-Ring (-025) [ .070 C.S. X 1.176 ID]

GREASE:  
THIN LAYER  
OF SLICK HONEY

GREASE:  
THIN LAYER  
OF SLICK HONEY

815-02-188-KIT  
Damping Adj Assy: 2021 Shock, Cartridge, LSR

TORQUE:  
60±5 in-lb

IMPORTANT:  
ENSURE O-RINGS ARE  
INSTALLED IN CORRECT GROOVES

IMPORTANT:  
ENSURE O-RING IS  
INSTALLED IN CORRECT GROOVE

SECTION A-A

**FOX** FOX Factory, Inc. Ph 831-768-1100  
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE  
Eyelet Assy: 2024 DHX2 / FX2,  
Trunion, No CBV, No 2-Pos

SIZE DWG. NO. **C** 808-14-086-KIT

PLOT SCALE 2:1 SHEET 1 OF 1

- PROPRIETARY -  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

4

3

2

ProE ASSEM