



REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

TORQUE:
65±5 IN-LB

241-00-020
Fastener, Custom: Cover, Nut 011 RC2

241-00-022
Fastener, Custom: Nut, Bottom, 011 RC2

241-01-011
Fastener, Custom: Crush Washer, Plastic, 13mm

TORQUE:
5.0±0.5 IN-LB
LOCTITE:
BLUE 242
ONE DROP

018-01-004-A
Fastener, Standard: Screw [#8-32 X 0.250 TLG]

210-03-120
Knob, Rebound, 2011 36_40

029-08-053
Seals: O-Ring [15mm ID x 1.5mm CS] Metric, N-70, Static

820-05-377-KIT
2016 FIT4 Bottom Stud Interface Parts, RC

CARTRIDGE ASSY

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

TORQUE:
220±5 IN-LB

GREASE:
THIN LAYER
BLUE MARINE

TORQUE:
11±3 IN-LB

036-01-043
Seals: U-Cup, Shore 70A, 2013 Fit-CTD and CTD-ADJ

210-03-175
Knob, Low Speed Compression, 2016 RC

019-01-095
Fastener, Standard (Metric): Screw [M3 X 6mm] SHCS, Patchlock

820-05-348-KIT
2016 FIT4 TopCap Interface Parts, RC

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX FOX Factory, Inc. Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
**2016 40 RC
FIT4 Cart Assy Complete**

SIZE DWG. NO.
D

PLOT SCALE 1.00:1 SHEET 1 OF 1