



TORQUE: 50±5 IN. LB.

210-22-523
REBOUND KNOB

TORQUE: 5.0±1.0 IN. LB.

LOCTITE:
BLUE 242
ONE DROP

018-01-004-A
Fastener, Standard: Screw [#8-32 X 0.250 TLG]

241-00-005
BOTTOM NUT

241-01-002-C
CRUSH WASHER

820-05-334-KIT
BASE STUD INTERFACE PARTS

CARTRIDGE ASSY

IMPORTANT:
NOTE U-CUP
ORIENTATION

DETAIL A
SCALE 3.000

SEE DETAIL A

820-05-332-KIT
2016 FIT4 TopCap Interface Parts F-S Remote

9 DO NOT TIGHTEN FASTENER AGAINST COMPRESSION ADJUST KNOB HARD STOP,
USE TOOL TO PREVENT KNOB FROM TURNING

019-01-095 9
Fastener, Standard (Metric): Screw [M3 X 6mm] SHCS, Patchlock

210-22-946
Remote Compression Adjust Knob, F-S, FIT4

GREASE:
THIN LAYER OF
BLUE MARINE GREASE

TORQUE:
220±5 IN. LB.

210-22-947
Damping Adjust Part: Housing, Remote, Hubless, FIT4

039-00-291
Spring: Torsion 2013 Damper CTD Remote, .048 Square Wire, 0.600 Mean Coil Diam (

002-02-050
Bearing: External [0.115 W X 0.810 OD X 0.030 TH, Ø 0.750 Bore] Turcon,Blue,Ring

036-01-044
Seals: U-Cup, Shore 70A, 2013 CTD-ADJ, Remote Fit-CTD and Remote O/C-CTD

019-01-088
Set Screw [M4x4mm], SST, Cup Point, Patchlock

210-22-945
Cable Pulley, Remote, F-S, FIT4

TORQUE:
11±3 IN. LB.

IMPORTANT:
DO NOT ALLOW PULLEY
TO ROTATE WHILE TORQUING

PROPRIETARY - PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX Factory, Inc. Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

**2016 Factory Series
Remote FIT4 Cart Assy Complete**

SIZE DWG. NO. D
PLOT SCALE 1.00:1 SHEET 1 OF 1