



222-01-316  
Piston: Lockout, Float DPS [.200 TLG, M20 X 0.5] 416SS

044-04-055  
Valve: [.550 OD X 0.252 ID X 0.0045 TH]

044-04-050  
Valve: [.500 OD X .252 ID X .0045 TH]

210-10-104  
Piston Bolt: Dish WRD w/ check [1/4-28 X 5/8 Hex]

TORQUE:  
22±2 IN.LB.  
Custom socket: 398-00-638

TORQUE:  
60±5 IN.LB.  
Custom Socket: 398-00-637

805-02-031  
Piston Assembly: 2016 Float DPS, [Ø 0.940 Bore] w/ Glyde Ring

- NOTES: (UNLESS OTHERWISE SPECIFIED)
- 1. SHOCK SHOULD HAVE 12-15 REBOUND CLICKS
  - [2] 1 OR 2 SPACERS MAY BE ADDED OR REMOVED TO ADJUST NUMBER OF REBOUND CLICKS .030" MIN SPACING
  - [3] 1 OR 2 SPACERS MAY BE ADDED OR REMOVED TO ADJUST NUMBER OF REBOUND CLICKS .010" MIN SPACING
  - [4] 1 OR 2 SPACERS MAY BE ADDED OR REMOVED TO ADJUST LOCKOUT PLATE LIFT .010" MIN SPACING
  - [5] USE .030-.047 LIFT SPEC FROM CLOSED TO OPEN FOR REMOTES WITH 210-30-090 CAM (TREK)

044-06-085  
Valve: [.850 X .252 X .006]

044-04-060  
Valve: [.600 OD X .252 ID X .0045 TH]

044-06-060  
Valve: [.600 X .252 X .006]

044-04-080  
Valve: [.800 OD X .252 ID X .0045 TH]

050-01-011 [2]  
Plate: Back-Up [0.400 OD X 0.252 ID X 0.020 TH, Ø 0.375 Shaft] Steel

044-10-035 [2]  
Valve: [.350 OD X .252 ID X 0.010 TH]

044-04-050  
Valve: [.500 OD X .252 ID X .0045 TH]

044-04-070  
Valve: [.700 OD X .252 ID X .0045 TH]

210-10-098  
Damping Adjust Part: Float MY2013 Check Piston [.740 OD X .252 ID X .110 TH]

PROPRIETARY  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

**FOX** FOX Factory, Inc. Ph 831-768-1100  
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE  
**Valving Assy: 2017 Float DPS,  
R/C, CF, RM, CMF [.940 Bore]**

SIZE DWG. NO.  
**C 807-06-191-KIT**

PLOT SCALE 2.00:1 SHEET 1 OF 1