



NOTE KNOB ORIENTATION [3]

- [2] NOTE PART IDENTIFICATION GROOVES FOR LV DOWN CONFIGURATIONS.
- [3] FOX LOGO AS SHOWN WHEN KNOB IN MIDDLE OF ADJUSTMENT RANGE.
- [4] PULLEY TO BE FULLY SEATED AGAINST COMPRESSION CAM FLANGE.
- [5] APPLY THIN LAYER SLICK HONEY TO INSTALL ON AIR VALVE. APPLY THIN LAYER FLOAT FLUID ON INSTALLED AIR VALVE O-RING PRIOR TO AIR VALVE INSTALLATION.
- [6] BLACK TORX SET SCREW FIXES PULLEY TO CAM.
- [7] STAINLESS HEX SET SCREW FIXES CABLE TO PULLEY.

PROPRIETARY - THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

**FOX** **FOX Factory, Inc.** Ph 831-768-1100  
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE  
**Eyelet, LV UP  
2017 FLOAT Remote**

SIZE DWG. NO.  
**C 808-17-314-KIT**

PLOT SCALE | .50:1 | SHEET 1 OF 2