



RESERVOIR BODY

805-00-078-KIT  
Piston Assembly: MY14 Floating w/ Bleed [1.070 Bore] Al 6061, Type III Clear Ano

813-00-082-KIT  
Rezi End Cap Assy: Float X, Non Adjust, Wire Ring, Pellet [1.070 Bore] Black Ano III  
038-01-024  
Retaining Ring: Wire [1.200 OD X .040 CS]  
210-22-748  
Lockring: Rezi End Cap: 2014 Float X [1.175 TLG, 1.200 OD] Typell, Black

TORQUE:  
45±5 IN.LB.

GREASE:  
THIN LAYER  
OF SLICK HONEY

029-03-022  
O-Ring (-022) [1.070 C.S. X .989 ID]

AIR SLEEVE ASSY

OIL:  
2±.2cc FLOAT FLUID.

010-00-011  
Air Valve Parts: Pellet [Ø 0.275 X 0.125 TLG] nitrile durometer A 90

TORQUE:  
14±2 IN.LB.

010-00-010  
Pellet Retainer [5/16-24, .220 TLG]

010-01-003  
Ball [Ø 0.1875] Delrin

BODY

VALVE ASSY

BEARING ASSY

210-03-192  
RD Adj Insert, 2014 Float X, 28deg Taper [1.126 Hex, .175 TLG, 6x .059 thru]

METERING ROD

029-08-004  
Seals: O-Ring [3.0MM ID x 1.0MM CS] Metric, N-70, Static

SHAFT

LOCTITE:  
RED 277

TORQUE:  
110±5 IN.LB.

029-03-110  
O-Ring (-110) [1.103 C.S. X .362 ID]

041-15-110  
Valve: [1.100 OD X .504 ID X .015 TH]

VOLUME SPACER

EYELET ASSY

043-10-941  
Valve: [1.941 OD X .675 ID X .010 TH]

TORQUE:  
20±2 FT.LB.

LOCTITE:  
BLUE 242

039-00-054  
Spring: [1.440 TLG X .938 OD]

GREASE:  
THIN LAYER  
SLICK HONEY

TORQUE:  
HAND TIGHT  
AFTER NITROGEN

TORQUE:  
20±2 FT.LB.

OIL:  
THIN LAYER  
OF SILKOLINE

OIL:  
THIN LAYER  
OF FLOAT FLUID

TORQUE:  
60±5 IN.LB.

TORQUE:  
60±5 IN.LB.

**FOX Factory, Inc.**  
130 Hangar Way, Watsonville, CA 95076 USA  
Ph 831-768-1100  
Fax 831-768-9312

2014, FLOAT X

PROPRIETARY - PROPRIETARY INFORMATION  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

SIZE DWG. NO.  
D  
PLOT SCALE 1.00:1  
SHEET 1 OF 2