

4

3

2

1

DAMPER SHAFT ASSEMBLIES:
 820-03-468-KIT: 2016 32 29in FIT4 Damper Shaft Assy
 820-03-467-KIT: 2016 32 26in and 27.5in FIT4 Damper Shaft Assy
 820-03-333-KIT: 2016 32 26in and 27.5in FIT4 Damper Shaft Assy, Long Travel

TOPCAP ASSEMBLIES:
 820-05-422-KIT: 2016 32 FIT4 F-S Topcap Assy, VC45, Black Ano
 820-05-424-KIT: 2018 32 FIT4 F-S Topcap Assy, Long Travel, E18, Black Ano

038-01-073
 Retaining Ring: Wire [1.280 OD X .024 CS] SS

210-22-920
 Compression Adjust Coupler, F-S, FIT4

029-08-068
 Seals: O-Ring [3.0MM ID x 1.5MM CS] Metric, N-70, Static

TORQUE:
 55±5 IN.LB.

PRESSURE TUBES:
 207-11-102: (T) Pressure Tube, 15.5 Bore, 120 Max Travel, FIT4
 207-11-103: (T) Pressure Tube, 15.5 Bore, 130 Max Travel, FIT4

039-00-243
 Spring: Detent [.138 TLG X .087 OD X 48 lb/in] SS

010-01-012
 Air Valve Parts: Ball [Ø 0.1094] E52100 Grade 25 Steel, Chrome

GREASE:
 THIN LAYER
 OF SLICK HONEY ON BALL

ASSEMBLE THESE PARTS AFTER OIL FILL
 COMPRESS DAMPER SHAFT 3IN BEFORE SEALING DAMPER

FOX Factory, Inc.
 130 Hangar Way, Watsonville, CA 95076 USA
 Ph 831-768-1100
 Fax 831-768-9312

TITLE
**2018 32mm F-S FIT4
 Cartridge Assemblies**

SIZE DWG. NO.
C
 PLOT SCALE | .00 : 1 | SHEET | OF |

PROPRIETARY
 THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
 THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
 FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

ProE ASSEM