

4

3

2

1

019-01-115
Fastener Standard (Metric): Screw
[M2.5 X 6mm] Socket Head Cap, SS

820-05-454-KIT
2018 Grip P-S Topcap Interface Parts

039-00-375
Spring: Wave, 4 Turns, [.562 Bpre, .375 Shaft, .260 Height, 37.0 lb/in] SS

210-24-123
Damping Adj Part: Detent, Molded, Grip

(210-24-123)
036-01-044
Seals: U-Cip, Shore 70A, 2013 CTD-ADJ, Remote O/C-CTD

GREASE:
THIN LAYER
OF SLICK HONEY

TORQUE:
4±1 in-lb

210-24-249
Damping Adj Part: Knob, Comp Selector, 34/36 Grip

CARTRIDGE ASSY

GREASE:
LIBERALLY WITH
SLICK HONEY

(039-00-375)

(210-24-123)

(036-01-044) NOTE ORIENTAION

(210-24-123)

ENGAGE 2X FEATURES

SECTION A-A
SCALE 2.500

241-01-002-C
Fastener, Custom: Crush Washer, Plastic, R_RL_RLC

241-00-005
Fastener, Custom: Nut, Bottom, R_RL_RLC

BOTTOM STUD INTERFACE PARTS:
820-05-506-KIT: 2019 34 SC Bottom Stud Interface Parts, 29in Fork
820-05-507-KIT: 2019 34 SC Bottom Stud Interface Parts, 27.5in Fork

REBOUND KNOBS:
210-24-367: Knob: Rebound Adj, Extruded, 2019 FIT4 Lightweight, 34, 29in
210-24-375: Knob: Rebound Adj, Extruded, 2019 FIT4 Lightweight, 34, 27.5in

019-01-048
Fastener, Standard (Metric): Screw [M2.5 X 6mm] Socket Head Cap, Stainless

LOCTITE:
BLUE 242 OR 243
ONE DROP

TORQUE:
5.0±0.5 IN.LB.

TORQUE:
50in-lb

REFERENCE ONLY
(FOR INSTALLATION
INTO FORK)

IMPORTANT:
INSTALL O-RING IN THIS LOCATION

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX Factory, Inc. Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE **2019 34 SC Grip Cartridge Assemblies Complete**

SIZE DWG. NO. **C**

PLOT SCALE 0.75:1 SHEET 1 OF 2