



029-08-022
Seals: O-Ring [8.0MM ID x 1.0MM CS] Metric, N-70, Static

234-04-913
Base Stud: FLOAT NA 2, External Thread, Vented

820-02-330-KIT
Neg Plate Subassembly, FLOAT NA 2, 40

GREASE:
THIN LAYER
OF SLICK HONEY

TORQUE:
50±5 IN.LB.

234-04-629
Topout Bumper, FLOAT NA

LOCTITE:
1-2 DROPS
RED 262

SHAFT

TORQUE:
120±10 IN.LB.

TORQUE:
50±5 IN.LB.

GREASE:
THIN LAYER
OF SLICK HONEY

IMPORTANT:
NOTE: VERIFY SEAL IS NOT
TWISTED AFTER INSTALL

GREASE:
THIN LAYER
OF SLICK HONEY

GREASE:
THIN LAYER
OF SLICK HONEY

LOCTITE:
1-2 DROPS
RED 262

029-08-060
Seals: O-Ring [6.0mm ID x 1.5mm CS] Metric, N-70, Static

234-04-724
Piston Base, FLOAT NA 2, 40

002-02-060
Piston Band, LF, FLOAT NA 2, 40

035-00-217
Seals: Q-Ring [(-217) .139 C.S. X 1.171 ID]

234-44-110
Piston, FLOAT NA 2, 40, 7075

FOX **FOX Factory, Inc.** Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
2019 40 FLOAT
Air Shaft Assemblies

SIZE DWG. NO.

C

PLOT SCALE 0.75:1

SHEET 1 OF 1

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.