

4

3

2

1

Topcap and Shaft Press-fit sub-assembly  
(Not available outside of 820-05-510-KIT Topcap Assembly)

029-03-026-A  
Seals: O-Ring [(-026) .070 C.S. X 1.239 ID] Standard, N-70, Static

229-10-701  
Shaft, HSC Grip F-S, 40 203

210-03-281  
Damping Adjust Part: Needle, LSC, Grip F-S, 40 203

029-08-068  
Seals: O-Ring [3.0MM ID x 1.5MM CS] Metric, N-70, Static

210-24-245  
Damping Adj Part: Coupler, LSC, Grip2

038-01-073  
Retaining Ring: Wire [1.280 OD X .024 CS] SS

241-02-101  
Fastener, Custom (Metric): Bolt Piston Comp Grip2

039-00-398  
Spring, Comp Check, Grip2

045-00-151  
Valve: Metric [18.50mm OD X 5.55mm ID X 0.25mm THK] Custom, Check

029-08-188  
Seals: O-Ring [17mm ID X 1.5mm CS] N-90, Static

222-01-295  
Piston Damping Comp 20.0 Bore

820-03-530-KIT  
2019 Grip2 Compression Valving

029-08-060  
Seals: O-Ring [6.0mm ID x 1.5mm CS] Metric, N-70, Static

241-02-115  
Fastener Custom: Pin, Grip2

210-24-241  
Damping Adj Part: Valve Loader, HSC, Grip2

029-03-011  
Seals: O-Ring [(-011) .070 C.S. X .301 ID] Standard, N-70, Static

223-00-049  
Piston Floating: IFP, Grip2

029-08-196  
Seals: O-Ring [16.0mm ID X 2.0mm CS] Metric, N-70, Dynamic

231-00-111  
Sleeve: Isolator, Spring, OD, Grip 40

039-00-436  
Spring, Piston, Floating, Grip 203

231-00-012  
Sleeve: Isolator, Spring, ID, Grip 40

PROPRIETARY - THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

SIZE	DWG. NO.	REV.
C	820-05-510-KIT	B
PLOT SCALE	1.5:1	SHEET

4

3

2

1