

4

3

2

1

241-00-005  
Fastener, Custom: Nut, Bottom, R\_RL\_RLC

241-01-002  
Fastener, Custom: Crush Washer, Plastic, R\_RL\_RLC

TORQUE:  
50±5 IN.LB.  
(INTO FORK CHASSIS)

IMPORTANT:  
INSPECT 100% THAT RETAINING RING  
IS FULLY INSTALLED INTO GROOVE FULL 360°

038-00-137  
Retaining Ring: Internal, Smalley HHM-38-S02, Hoopster, 302 SS

820-02-520-KIT  
Air Shaft Assy, 40, 203mm, FLOAT NA 2.1

APPLY GREASE AROUND PISTON, TRANSFER SHAFT, ON 10MM SHAFT  
BETWEEN BUMPER AND NEG PLATE, AND A THIN LAYER ON ENTIRE  
LENGTH OF PISTON BORE OF UPPER TUBE ID.

TORQUE:  
220±5 IN.LB.  
(INTO FORK CHASSIS)

234-04-726  
Volume Spacer, FLOAT NA 2, 40

029-03-008  
O-Ring (-008) [.070 C.S. X .176 ID]

820-05-346-KIT  
Topcap Assy, FLOAT NA 2, 40, Black

GREASE:  
THIN LAYER  
OF SLICK HONEY

210-24-433  
2019 Marzocchi Bomber Z1 & 58 Air Knob

**FOX** FOX Factory, Inc. Ph 831-768-1100  
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE  
Air Spring Assy, 2019 Marzocchi  
Bomber 58, 40, 203mm, FLOAT NA 2

SIZE DWG. NO.  
C  
PLOT SCALE | .00:1 | SHEET | OF |

- PROPRIETARY -  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

4

3

2

1

ProE ASSEM