



207-11-131  
Pressure Tube, [15.5mm Ø X 170mm TLG]  
LIVE Lightweight 32 26/27.5/29 80-100

820-03-623-KIT  
2020 34 SC 27.5in and 29in 120mm Max, 8mm, LIVE Damper Shaft Assy

TORQUE:  
55±5 IN-LB

ASSEMBLE 002-02-011 Glide Band AT THIS LEVEL

038-00-065  
Retaining Ring: Snap, Smalley, Internal, Custom, Ø.923 BORE

241-01-029  
Bladder retainer, 011 RC2

210-22-420  
Lower Bladder Ring, Snap Ring, 011 RC2

210-24-002  
Bladder, 010 RL-RLC

210-22-887  
Bladder Seal Ring Lower, FIT4

038-00-142  
Retaining Ring: Snap, Smalley, Internal, VH-62, Ø.610 Bore

(040-06-060)

039-00-143  
Spring, Comp Check, 010 RL-RLC

040-06-060  
Valve: [.600 OD X .377 ID X .006 TH]

029-08-072  
Seals: O-Ring [23.0MM ID x 1.5MM CS] Metric, N-70, Static

029-08-013  
Seals: O-Ring [24.0MM ID x 1.5MM CS] Metric, N-70, Static

820-03-549-KIT  
2018 LIVE Fork Compression Valving, CL, BL, 2 Bleed

815-00-077-KIT  
Service Set: 2019 LIVE Compression Housing Sub Assy

241-02-125  
Fastener, Custom, (Metric): [M2 x 4MM] Socket, Flathead, SS, Patchlock

010-01-000  
Ball [Ø 0.1250] Steel

018-01-004  
Fastener, Standard: Screw [#8-32 X 0.250 TLG] 303 SS, Socket Set Half Dog Point

038-01-075  
Retaining Ring: Wire, Main Housing, 2017 LIVE

029-03-024-A  
Seals: O-Ring [(-024) .070 C.S. X 1.114 ID] Standard, N-70, Static

210-24-399  
Solenoid End Cap Retainer Plate, Live Valve

TORQUE:  
2.0±0.5 IN-LB

(241-02-125)  
INSTALL AFTER OIL FILL

TORQUE:  
40±5 IN-LB

TORQUE:  
55±5 IN-LB

210-24-114  
Topcap, 34, 2017 LIVE Fork, Short

**FOX Factory, Inc.**  
130 Hangar Way, Watsonville, CA 95076 USA  
Ph 831-768-1100  
Fax 831-768-9312

TITLE  
**2020 LIVE Valve Cartridge 34mm SC**  
(AM: Scott Spark/ Spark RC)

SIZE DWG. NO.  
D  
PLOT SCALE NONE SHEET 1 OF 1

PROPRIETARY - THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.