

4

3

2

1

.059-.065 VALVE STACK HEIGHT  
[1,50-1,65]

Spring: Conical, LIVE Shock, Check [1.25TLG, 3lbf/in, .34in ID X .64in ID], 302 S

IMPORTANT:  
ORIENT AS SHOWN  
ROUNDED SIDE TOWARD VALVES

CHECK:  
ENSURE VALVE LIFTS  
FREELY AFTER TORQUE

CHECK:  
ENSURE SPRING IS FULLY CAPTURED  
UNDER BOLT FLANGE

SECTION A-A  
SCALE 6:1

210-24-228  
Bolt: HSC piston, 2017 LIVE Shock, M6 X 1, SS

NOTE:  
ALTERNATE ASSEMBLY: SPRING CAN BE INSTALLED AFTER TORQUE  
TO MAKE VALVE STACK ASSEMBLY EASIER

039-00-386

045-15-820

Valve: Metric [20.0mm OD X 8.0mm ID X 0.15mm TH]

Piston: HSC, Reservoir IFP Side, 2017 LIVE Shock, M22 X 1 [.930 OD X 6mm ID]

045-15-608

Valve: Metric [8.0mm OD X 6.0mm ID X 0.15mm TH]

045-00-201

Valve: Metric, Bleed Slot 2 [14mm OD X 6mm X ID 0.1mm TH]

045-15-614

Valve: Metric [14.0mm OD X 6.0mm ID X 0.15mm TH]

045-15-612

Valve: Metric [12.0mm OD X 6.0mm ID X 0.15mm TH]

045-15-610

Valve: Metric [10.0mm OD X 6.0mm ID X 0.15mm TH]

045-20-608

Valve: Metric [8.0mm OD X 6.0mm ID X 0.20mm TH]

045-10-608

Valve: Metric [8.0mm OD X 6.0mm ID X 0.10mm TH]

045-30-608

Valve: Metric [8.0mm OD X 6.0mm ID X 0.30mm TH]

045-30-608

Valve: Metric [8.0mm OD X 6.0mm ID X 0.30mm TH]

019-02-026

Fastener, Custom (Metric): Nut, [M6 x 1.0], 2017 LIVE, SS

TORQUE:  
40±5 IN-LB

**FOX** FOX Factory, Inc. Ph 831-768-1100  
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE  
Damping Adj Assy: 2019 Live Shock, Lockout Blowoff, BL, 2 Bleed

SIZE DWG. NO. 815-02-122-KIT  
PLOT SCALE 2:1 SHEET 1 OF 1

PROPRIETARY -  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

4

3

2

ProE ASSEM