



SECTION A-A

TORQUE:  
10-15 IN-LBF

NOTE:  
INSTALL DURING DAMPER ASSEMBLY  
AFTER OIL FILL

GREASE:  
THIN LAYER  
OF SLICK HONEY

010-01-000  
Ball [Ø 0.1250] Steel

018-01-034  
Set Screw [#8-32 X 0.125 TLG] Flat Point, SS

Bearing Housing, 2020 SuperStrut

029-08-123  
Seals: O-ring [8.5mm ID x 2.5mm CS], Metric, Polyurethane 92A or 90A, Dynamic

029-08-213  
Seals: O-Ring [22.0mm x 1.5mm CS] Metric, Polyurethane, 90 Durometer, Static

Bearing, (T): Internal [9mm ID x 11mm OD x .440" TLG, 9mm Shaft]

Bearing: External [.113 W X 1.277 OD X .047 TH, Ø1.287 Bore] PTFE, Split

Seals: Q-Ring [(-214) .139 C.S. X 0.984 ID]

Bearing: External [.113 W X 1.277 OD  
0.47 TH, Ø1.287 Bore] PTFE, Split

PROPRIETARY - THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

|                                      |                |                                     |
|--------------------------------------|----------------|-------------------------------------|
|                                      |                | Ph 831-768-1100<br>Fax 831-768-9312 |
| TITLE: Bearing Assy, 2020 SuperStrut |                |                                     |
| SIZE DWG. NO. D                      | 812-06-095-KIT |                                     |
| PLOT SCALE 4:1                       | SHEET 1 OF 1   |                                     |