


PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FINAL TOPCAP AND COMP LEVER INSTALLATION INSTRUCTIONS:

- 1 AFTER OIL INSTALLATION, CYCLING DAMPER SHAFT AND PULLING DAMPER SHAFT TO FULL TOPOUT, INSTALL AND TORQUE TOPCAP ASSEMBLY TO 220 ± 5 IN-LBF.
- 2 GREASE O-RING INSIDE TOPCAP COUNTERBORE WITH THICK LAYER OF FOX BLUE GREASE.
- 3 TORQUE COMPRESSION NEEDLE TO 2.0 IN-LBF TO SEAT SHIMS AND COMP HAT, THEN OPEN 1/4 TURN. DO NOT COMPRESS FORK.
- 4 TORQUE COMPRESSION NEEDLE TO FINAL 8.0 ± 0.8 OZF-IN.
- 5 INSTALL LEVER TO ENGAGE THE OCTAGON OF THE COMP NEEDLE TO WHICHEVER IS CLOSEST TO 6 O'CLOCK WITHIN $\pm 23^\circ$ SPEC. IF THE CLOSEST ENGAGEMENT IS CW, AS THE LEVER IS BEING PUSHED DOWN AND THE TAB GETS CLOSE TO THE CROWN, ROTATE THE LEVER CCW TO THE 6 O'CLOCK POSITION BEFORE PUSHING THE LEVER ALL THE WAY DOWN. INSTALL AND TORQUE THE M2.5 SCREW (019-01-115) TO 11 ± 3 IN-LBF.



+23°
(MAX CW LEVER
INSTALL POSITION)

-23°
(MAX CCW LEVER
INSTALL POSITION)

2 GREASE:
AFTER O-RING IS INSTALLED, APPLY THICK
LAYER OF FOX BLUE GREASE

3 4 TORQUE:
 8.0 ± 0.8 OZF-IN
(SEE INSTRUCTIONS ABOVE)

1 TORQUE:
 220 ± 5 IN-LBF
(INTO FORK CHASSIS)

GREASE:
THIN LAYER
OF SLICK HONEY

5 TORQUE:
 11 ± 3 IN-LBF

135cc of 5wt. Teflon Infused Oil in Damper

820-03-636-KIT
2020 Marzocchi Z2 34 E-Bike+ RAIL 100-150 Damper Shaft Assy Complete

GREASE:
THIN LAYER
OF SLICK HONEY

GREASE:
THIN LAYER
OF SLICK HONEY

IMPORTANT:
INSPECT 100% THAT RETAINING RING
IS FULLY INSTALLED INTO GROOVE FULL 360°

TORQUE:
 50 ± 5 IN-LBF
(INTO FORK CHASSIS)

TORQUE:
 5.0 ± 0.5 IN-LBF

Retaining Ring: Internal, Smalley HHM-31-S02, Hoopster, 302 SS

Fastener, Custom: M8x1.0 Fine Thread Flanged Lock Nut

Rebound Knob, 2020 Marzocchi Z2 Rail Damper

Fastener, Standard: Screw [#8-32 X 0.250
TLG] 303 SS, Socket Set Half Dog Point

820-05-615-KIT

2020 Marzocchi Z2 34 Rail Bottom Stud Interface Parts

820-05-642-KIT
2020 Marzocchi Z2 34 E-Bike+ RAIL Topcap Comp Assy, Black Ano

Seals: O-Ring [22.5mm X 1.5mm CS] Metric, N-70, Static

Compression Lever, 2020 Marzocchi Z2 (34)

Fastener Standard (Metric): Screw [M2.5 X 6mm] Socket Head Cap, SS

820-05-614-KIT
2020 Marzocchi Z2 34 Rail Topcap Interface parts



2020 Marzocchi Z2 34 E-Bike+ RAIL
100-150 Travel Cart Assy Complete

SIZE C PART NO. 820-18-338-KIT

PLOT SCALE 1:1 SHEET 1 OF 1