

4

3

2

1

820-05-460-KIT  
2018 Grip P-S 32 Topcap Interface Parts

Spring: Wave, 4 Turns, [.562 Bpre, .375 Shaft, .260 Height, 37.0 lb/in] SS

Damping Adj Part: Detent, Molded, Grip

Damping Adj Part: Detent, Molded, Grip

Seals: U-Cip, Shore 70A, 2013 CTD-ADJ, Remote O/C-CTD

TORQUE:  
4±1 in-lb

GREASE:  
THIN LAYER  
OF SLICK HONEY

GREASE:  
LIBERALLY WITH  
SLICK HONEY

ENGAGE 2X FEATURES

SECTION A-A  
SCALE 2.500

BOTTOM STUD INTERFACE PARTS:  
820-05-374-KIT: 2017 Grip Bottom Stud Interface Parts  
820-05-326-KIT: 2017 34 29in Grip Bottom Stud Interface Parts

241-01-002-C  
Fastener, Custom: Crush Washer, Plastic, R\_RL\_RLC

241-00-005  
Fastener, Custom: Nut, Bottom, R\_RL\_RLC

REBOUND KNOBS:  
Knob: Rebound Adjust, Extruded, Red, Grip  
Knob: Rebound Adjust, Grip Extruded, Red, 29

TORQUE:  
5.0±0.5 IN.LB.

LOCTITE:  
BLUE 242 OR 243  
ONE DROP

TORQUE:  
50±5  
(IN-LB)

Fastener, Standard: Screw [#8-32 X 0.250 TLG] 303 SS, Socket Set Half Dog Point

		<b>FOX Factory, Inc.</b>	Ph 831-768-1100
		130 Hangar Way, Watsonville, CA 95076 USA	Fax 831-768-9312
TITLE	2021 32 GRIP CARTRIDGE ASSEMBLIES COMPLETE		
SIZE	DWG. NO.		
<b>C</b>			
PLOT SCALE	0.75:1	SHEET 1 OF 2	

- PROPRIETARY -  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

4

3

2

ProE ASSEM