



Damping Adjust Part: RD Knob, Float DPX2, Red

Seals: o-ring [15.5mm ID X 1.5mm CS], N-70, Static

Spring: Detent [.50 TLG, .312 OD, 1 lb/in]

BASE VALVE ASSEMBLY

SHAFT END EYELET

Spring: Detent [.50 TLG, .312 OD, 1 lb/in]

IMPORTANT: ADJUSTER IN END CAP MUST BE SET TO "ALL OUT" POSITION BEFORE INSTALLATION INTO EYELET

804-00-152-KIT

Seals: o-ring [15.5mm ID X 1.5mm CS], N-70, Static

Damping Adjust Part: CD Knob, FLOAT DPX2 Comp Adj., Blue

TORQUE: 110±5 IN LB

TORQUE: 90±5 IN LB

GREASE: THICK LAYER HIGH TEMP BLUE

804-00-152-KIT Eyelet Cap Assembly: DPX2, Rebound

IMPORTANT: ADJUSTER IN END CAP MUST BE SET TO "ALL OUT" POSITION BEFORE INSTALLATION INTO EYELET

TORQUE: 90±5 IN LB

GREASE: THICK LAYER HIGH TEMP BLUE

GREASE: THIN LAYER SLICK HONEY

O-Ring (-025) [1.070 C.S. X 1.176 ID]

GREASE: THIN LAYER SLICK HONEY

Seals: O-Ring [6.5mm ID x 1.5mm CS] Metric, N-70, Static

GREASE: THIN LAYER SLICK HONEY

Seals: O-Ring [10.0MM ID x 1.5MM CS] Metric, N-70, Static

Seals: O-Ring [(-032) .070 C.S. X 1.864 ID] Standard N674-70, Dynamic

GREASE: THIN LAYER SLICK HONEY

TORQUE: 35±5 IN LB

OIL: THIN LAYER FLOAT FLUID

802-00-007-KIT Air Valve Assy: Slim[M6 X .75, 1.150 TLG]

Air Valve Parts: Cap, Air Valve [.305-.32], Black, 6061

FOX Factory, Inc.
 130 Hangar Way, Watsonville, CA 95076 USA
 Ph 831-768-1100 Fax 831-768-9312

TITLE: Eyelet Assy: 2019 FLOAT DPX2 Comp Adj, Trunnion

SIZE DWG. NO. **808-17-402-KIT**

PLOT SCALE ~2:1 SHEET 1 OF 1

PROPRIETARY - THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.