

REFERENCE ONLY  
(FOR INSTALLATION  
INTO FORK)

TORQUE:  
80±5  
IN-LBS

REBOUND KNOB

TORQUE:  
5.0±1.0 IN-LB

LOCTITE:  
BLUE 243  
ONE DROP

Fastener, Standard: Screw [#8-32 X 0.250 TLG]

241-00-022  
Fastener, Custom: Nut, Bottom, 011

820-05-377-KIT  
2016 FIT4 Bottom Stud Interface Parts 36, 38 and 40

241-01-011  
Fastener, Custom: Crush Washer, Plastic, 13mm

REFERENCE ONLY  
(FOR INSTALLATION  
INTO FORK)

TORQUE:  
220±51N-LB

Seals: U-Cup, Shore 70A, 2013 Fit-CTD and CTD-ADJ

Compression Adjust Knob,F-S,FIT4

TORQUE:  
11±3 IN-LB

SEE DETAIL A FOR PARTS

GREASE:  
THIN LAYER  
BLUE MARINE

LOCKOUT KNOB

Fastener, Standard (Metric): Screw [M3 X 6mm] SHCS, Patchlock

820-05-330-KIT  
2016 FIT4 TopCap Interface Parts F-S

BALL DIA .078

Retaining Ring: External, 8.5mm Shaft, 302SST

Plate, Detent Spring Retainer, 2013 CTD Performance

Spring: Detent [.180 TLG X .090 OD X 100 lb/in] SS, LHW

GREASE:  
THIN LAYER OF  
BLUE MARINE ON BALL

DETAIL A  
SCALE 4.000

SEE DETAIL A

**FOX Factory, Inc.**  
130 Hangar Way, Watsonville, CA 95076 USA  
Ph 831-768-1100 Fax 831-768-9312

TITLE  
**2020 36, 140-180, FIT4 F-S,  
3 Pos Adj Cart Assy Complete**

SIZE DWG. NO.  
**820-18-242-KIT**

PLOT SCALE 1.00:1 SHEET 1 OF 1

PROPRIETARY  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.