



ALIGN TAB ON EYELET WITH KEYHOLE IN XV SLEEVE  
900-LEVEL SPECIFIES ORIENTATION

OUTER AIR SLEEVE

SHAFT-END EYELET

INNER AIR SLEEVE

HSR INNER SHAFT

DAMPER SHAFT

MAIN PISTON ASSY

805-00-124-KIT  
Piston Assembly: Floating [Ø 1.160 Bore, 0.475 TLG], Bleed Screw

OUTER BODY

812-06-106-KIT  
Bearing Assy: Negative Air Sealhead, 2021 FX2

227-09-037  
Reservoir: 2021 DHX2 / FX2 [1.160 Bore, 1.806 TLG]

INNER BODY

EYELET ASSY

ADD  $2 \pm .2$ cc 20 WT GOLD TO POSITIVE AIR CHAMBER  
ADD  $1 \pm .2$ cc 20 WT GOLD OIL TO NEGATIVE AIR CHAMBER

NITROGEN PRESSURE 100 +/- 10psi

**FOX Factory, Inc.**  
130 Hangar Way, Watsonville, CA 95076 USA  
Ph 831-768-1100  
Fax 831-768-9312

**2021 FLOAT X2**

SIZE DWG. NO. D  
PLOT SCALE 1.25:1 | SHEET 1 OF 2

PROPRIETARY - THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.