

4

3

2

1

044-08-050
Valve: [.500 OD X 0.252 ID X 0.008 TH]

045-00-074
Valve: Metric [13.2mm OD x 6.4mm ID x 0.15mm TH]

002-02-011
Glide Ring, 04 Slim R_RL_RLC_X

045-00-035
Valve: Metric [13.0mm OD X 8.1mm ID X 0.15mm TH]

039-00-336
Spring: [0.200 TLG X .400 ID X 0.50 lbs/in] Stainless Steel

210-22-248
Insert, Rebound, 09 36_40, Check Limiter

029-08-029
Seals: O-Ring [7.0MM ID x 1.0MM CS] Metric, N-70, Static

039-00-131
Spring: [.690 TLG X .242 ID X 22.0 lb/in] Stainless Steel

029-08-004
Seals: O-Ring [3.0MM ID x 1.0MM CS] Metric, N-70, Static

IMPORTANT:
VERIFY SHIMS
ARE NOT PINCHED

TORQUE:
55±5 IN.LB.

210-22-449
Bolt, Rebound Piston, RC2, NBO

222-01-099
Piston: Rebound, 36_40, Kidney, Radiused Step

TORQUE:
25±5 IN.LB.

LOCTITE:
ONE DROP OF
RED 262

GREASE:
THIN LAYER
OF SLICK HONEY

210-22-244
Damp Adj Part: Needle, Rebound, High-Flow, 6 Flutes

REBOUND TUBE

REBOUND SHAFT

820-03-450-KIT
Sealhead Assembly, 2015 10mm Shaft, SKF

LOCTITE:
ONE DROP OF
RED 262

820-03-167-KIT
Rebound Adjuster Assembly, 2011 RC2

GREASE:
THIN LAYER
OF SLICK HONEY ON BULLET

GREASE:
THIN LAYER
OF SLICK HONEY

TORQUE:
25±5 IN.LB.

FOX FOX Factory, Inc. Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
2015 36 RC2 Rebound Assy

SIZE DWG. NO.
C
PLOT SCALE | .00 : 1 | SHEET | OF |

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

4

3

2

1

ProE ASSEM