



TORQUE:
150±5 IN. LB.

210-03-120
REBOUND KNOB

TORQUE:
5.0±1.0 IN. LB.

LOCTITE:
BLUE 242
ONE DROP

018-01-004-A
Fastener, Standard: Screw [#8-32 X 0.250 TLG]

241-00-011
BOTTOM NUT

241-01-011
CRUSH WASHER

820-05-335-KIT
BASE STUD INTERFACE PARTS

CARTRIDGE ASSY

IMPORTANT:
NOTE U-CUP
ORIENTATION

DETAIL A
SCALE 3.000

SEE DETAIL A

820-05-332-KIT
2016 FIT4 TopCap Interface Parts F-S Remote

019-01-095
Fastener, Standard (Metric): Screw [M3 X 6mm] SHCS, Patchlock
DO NOT TIGHTEN FASTENER AGAINST COMPRESSION ADJUST KNOB HARD STOP,
USE TOOL TO PREVENT KNOB FROM TURNING

210-22-946
Remote Compression Adjust Knob, F-S, FIT4

GREASE:
THIN LAYER OF
BLUE MARINE GREASE

TORQUE:
220±5 IN. LB.

210-22-947
Damping Adjust Part: Housing, Remote, Hubless, FIT4

039-00-291
Spring: Torsion 2013 Damper CTD Remote, .048 Square Wire, 0.600 Mean Coil Diam (

002-02-050
Bearing: External [0.115 W X 0.810 OD X 0.030 TH, Ø 0.750 Bore] Turcon,Blue,Ring

036-01-044
Seals: U-Cup, Shore 70A, 2013 CTD-ADJ, Remote Fit-CTD and Remote O/C-CTD

019-01-088
Set Screw [M4x4mm], SST, Cup Point, Patchlock

210-22-945
Cable Pulley, Remote, F-S, FIT4

TORQUE:
11±3 IN. LB.

IMPORTANT:
DO NOT ALLOW PULLEY
TO ROTATE WHILE TORQUING

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

| | |
|--|-----------------------------------|
| FOX Factory, Inc. 130 Hangar Way, Watsonville, CA 95076 USA Ph 831-768-1100 Fax 831-768-9312 | |
| TITLE 2017 34 Factory Series Remote FIT4 Cart Assy Complete | |
| SIZE D | DWG. NO. 820-08-697-KIT |
| PLOT SCALE 1.00:1 | SHEET 1 OF 1 |