

4

3

2

1



Seals: O-Ring [8.0MM ID x 1.0MM CS] Metric, N-70, Static

234-04-655
Base Stud: Float, 0.305-48 Thread

Seals: O-Ring [6.0mm ID x 1.5mm CS] Metric, N-70, Static

029-08-060

029-08-022

TORQUE:
50±5 IN.LB.

LOCTITE:
RED 263, 2-3 DROPS
OR ON FEMALE THREAD

NO LOCTITE ON O-RING GLANDS

GREASE:
THIN LAYER
OF SLICK HONEY

820-02-405-KIT
Neg Plate Subassembly, FLOAT, 2018 32 Rhythm

IMPORTANT:
GROOVE FACES
PISTON

234-04-404
Topout Bumper, FLOAT NA

GREASE:
THIN LAYER
OF SLICK HONEY

Shafts:
229-10-289: Shaft, Float Air Spring, Hard Ano, Rhythm 32 120mm Travel
229-10-290: Shaft, Float Air Spring, Hard Ano, Rhythm 32 110mm Travel
229-10-291: Shaft, Float Air Spring, Hard Ano, Rhythm 32 100mm Travel
229-10-293: Shaft, Float Air Spring, Hard Ano, Rhythm 32 80mm Travel

018-05-057
Fastener, Standard: Flat Washer [10mm ID X 26 OD]

IMPORTANT:
PRESS PIN
UNTIL CENTERED

060-01-010
Pin: Spring [Ø 0.188 X 0.875 TLG] Spring Steel, Zinc

222-01-322
Piston, FLOAT Air Spring, 32 Rhythm, 2018

035-00-212
Seals: Q-Ring [(-212) 0.139 C.S. X 0.859 ID]

IMPORTANT:
VERIFY SEAL IS NOT
TWISTED AFTER INSTALL

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX		FOX Factory, Inc.		Ph 831-768-1100
		130 Hangar Way, Watsonville, CA 95076 USA		Fax 831-768-9312
TITLE				
2018 32mm 27.5in/29in 80-120				
Rhythm Air Shaft Assemblies				
SIZE DWG. NO.				
C				
PLOT SCALE .00 : 1			SHEET OF	

4

3

2

1