

4

3

2

1

**Damper Shaft Assemblies:**  
 820-03-334-KIT: 2016 34 26in and 27.5in and 29in FIT4 Damper Shaft Assy, 120 Max Travel  
 820-03-469-KIT: 2016 34 26in and 27.5in and 29in FIT4 Damper Shaft Assy

ASSEMBLE 002-02-011 AT THIS LEVEL

TORQUE:  
 55±5 IN.LB.

**Topcap Assemblies:**  
 820-05-451-KIT: 2018 34 FIT4 F-S Topcap Assy, Remote, U-Cup, 2 Position, Push-Lock  
 820-05-487-KIT: 2018 34 FIT4 F-S Topcap Assy, Remote, U-Cup, 2 Position, Push-Unlock  
 820-05-464-KIT: 2018 34 FIT4 F-S Topcap Assy, Remote, U-Cup, 3 Position

038-01-073  
 Retaining Ring: Wire [ .280 OD X .024 CS ] SS

210-22-920  
 Compression Adjust Coupler, F-S, FIT4

029-08-068  
 Seals: O-Ring [ 3.0MM ID x 1.5MM CS ] Metric, N-70, Static

TORQUE:  
 55±5 IN.LB.

207-11-106  
 (T) Pressure Tube, 15.5 Bore, 160 Max Travel, FIT4

039-00-243  
 Spring: Detent [ .138 TLG X .087 OD X 48 lb/in ] SS

010-01-012  
 Air Valve Parts: Ball [ Ø 0.1094 ] E52100 Grade 25 Steel, Chrome

GREASE:  
 THIN LAYER  
 OF SLICK HONEY ON BALL

COMPRESS DAMPER SHAFT 3IN BEFORE SEALING DAMPER

- PROPRIETARY -  
 THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
 THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
 FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

		<b>FOX Factory, Inc.</b>	Ph 831-768-1100
		130 Hangar Way, Watsonville, CA 95076 USA	Fax 831-768-9312
TITLE			
2018 34mm 26in/27.5in/29in 120 & 130-160			
F-S FIT4 E18 Remote Cartridge Assemblies			
SIZE DWG. NO.			
<b>C</b>			
PLOT SCALE   .00 : 1		SHEET   OF   1	