

4

3

2

1

039-00-320  
Spring, Comp., [0.109 OD x 0.075 ID x 0.340 TLG], 21 lb/in, 2014.5 40 Air Bleed

Air Release Button, 2014.5 40

! IMPORTANT:  
PRESS HOUSING DOWN EVENLY TO LOWER LEG BEFORE  
EVENLY TIGHTENING DOWN THE M3 SCREWS

GREASE:  
ADD A SMALL AMOUNT OF SLICK HONEY GREASE (025-01-008)  
INTO BORE TO RETAIN SPRING DURING ASSY.

GREASE:  
AFTER INSTALLING ON BUTTON (210-22-827),  
APPLY THICK COAT OF SLICK HONEY GREASE

029-08-004  
Seals: O-Ring [3.0MM ID x 1.0MM CS] Metric, N-70, Static

GREASE:  
AFTER INSTALLING ON HOUSING (210-22-826),  
APPLY THICK COAT OF SLICK HONEY GREASE

029-08-168  
O-Ring [5.5mm X 1.5mm CS] Metric, Polyurethane-70, Static

(241-02-059)

Air Release Housing, 2014.5 40

TORQUE:  
8±1 IN.LB.

241-02-059  
Fastener, Custom: Screw, M3 X 5, SHCS, Black Zinc

**FOX** FOX Factory, Inc. Ph 831-768-1100  
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE  
2015 40 Air Release  
Button Assembly

SIZE DWG. NO.  
C 820-09-003-KIT

PLOT SCALE 4.00:1 SHEET 1 OF 1

- PROPRIETARY -  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

4

3

2

1

ProE ASSEM