



029-08-022  
Seals: O-Ring [8.0MM ID x 1.0MM CS] Metric, N-70, Static

234-04-913  
Base Stud: FLOAT NA 2, External Thread, Vented

820-02-330-KIT  
Neg Plate Subassembly, FLOAT NA 2, 40

GREASE:  
THIN LAYER  
OF SLICK HONEY

TORQUE:  
50±5 IN.LB.

234-04-629  
Topout Bumper, FLOAT NA

LOCTITE:  
1-2 DROPS  
RED 262

NO LOCTITE ON O-RING GLANDS

SHAFTS:  
229-10-409: Shaft, FLOAT NA 2, Internal Thread, 40 203mm  
229-10-412: Shaft, FLOAT NA 2, Internal Thread, 40 190mm

GREASE:  
THIN LAYER  
OF SLICK HONEY

LOCTITE:  
1-2 DROPS  
RED 262

NO LOCTITE ON O-RING GLANDS

029-08-060  
Seals: O-Ring [6.0mm ID x 1.5mm CS] Metric, N-70, Static

234-04-724  
Piston Base, FLOAT NA 2, 40

002-02-060  
Piston Band, LF, FLOAT NA 2, 40

035-00-217  
Seals: Q-Ring [(-217) .139 C.S. X 1.171 ID]

234-04-723  
Piston, FLOAT NA 2, 40

TORQUE:  
120±10 IN.LB.

TORQUE:  
50±5 IN.LB.

GREASE:  
THIN LAYER  
OF SLICK HONEY

IMPORTANT:  
NOTE: VERIFY SEAL IS NOT  
TWISTED AFTER INSTALL

GREASE:  
THIN LAYER  
OF SLICK HONEY

**FOX** **FOX Factory, Inc.** Ph 831-768-1100  
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE  
**Air Shaft Assemblies, 40,  
190mm and 203mm, FLOAT NA 2**

SIZE DWG. NO.

**C**

PLOT SCALE 0.75:1

SHEET 1 OF 1

PROPRIETARY  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.