

4

3

2

1

241-00-005
Fastener, Custom: Nut, Bottom, R_RL_RLC

241-01-002
Fastener, Custom: Crush Washer, Plastic, R_RL_RLC

TORQUE:
50±5 IN.LB.
(INTO FORK CHASSIS)

IMPORTANT:
INSPECT 100% THAT RETAINING RING
IS FULLY INSTALLED INTO GROOVE FULL 360°

038-00-137
Retaining Ring: Internal, Smalley HHM-38-S02, Hoopster, 302 SS

AIR SHAFT ASSEMBLIES:
820-02-349-KIT: Air Shaft Assy, 40, 203mm, FLOAT NA2
820-02-462-KIT: Air Shaft Assy, 2019 40, 190mm, FLOAT NA 2

029-03-008
O-Ring (-008) [.070 C.S. X .176 ID]

820-05-346-KIT
Topcap Assy, FLOAT NA 2, 40, Black

APPLY GREASE AROUND PISTON, TRANSFER SHAFT, ON 10MM SHAFT BETWEEN BUMPER AND NEG PLATE, AND A THIN LAYER OF PISTON BORE OF UPPER TUBE ID.

TORQUE:
220±5 IN.LB.
(INTO FORK CHASSIS)

234-04-726
Volume Spacer, FLOAT NA 2, 40

234-04-551
(T) Spring Hardware: 2014 40 FLOAT Air Topcap, Al, Blue Ano

GREASE:
THIN LAYER
OF SLICK HONEY

FOX FOX Factory, Inc. Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE
**Air Spring Assemblies, 2018, 40
190mm and 203mm, FLOAT NA 2**

- PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

SIZE DWG. NO.
C

PLOT SCALE | .00:1 | SHEET | OF |

4

3

2

Pr oE ASSEM