



RESERVOIR 300±10PSI PRESSURE

RESERVOIRS:
 227-09-024: Reservoir: 2011 Van R, RC [1.070 Bore, 2.400 TLG, .940 Piston bore] Black Ano, Type III Class 2 w/ Seal
 227-09-025: Reservoir: 2011 Van R, RC [1.070 Bore, 2.570 TLG, .940 Piston bore] Black Ano, Type III Class 2 w/ Seal (FOR 10.5 X 3.5 ONLY)

039-00-167
 Spring: Wave [1.50 OD X 3500 lb/in]

815-02-015-KIT
 Damping Adj Assy: 2011 VAN RC

TORQUE:
 30±2 FT.LB.

LOCTITE:
 BLUE 242

GREASE:
 THIN LAYER

805-00-027-KIT
 Piston Asm: Floating [Ø1.070 Bore, .325 TLG]

813-00-059-KIT
 Reservoir End Cap Asm: 07 Non Adjust, Wire Ring, Pellet [1.070 Bore]

038-01-024
 Retaining Ring: Wire [1.200 OD X .040 CS]

TORQUE:
 35±2 FT.LB.

GREASE:
 THIN LAYER

808-14-067-KIT
 Eyelet Asm: [Ø.500 Shaft X 1.463 TLG]

234-00-102
 Spring Retainer: Slotted [1.070 Bore, .500 Shaft, 1.850 OD X .275 TLG]

029-05-105
 O-Ring [1.050 C.S. X .154 ID]

SHAFT

REBOUND METERING ROD

008-01-016
 Bumper: B/O [Ø.498 Shaft, .400 TLG] Nitrile 60A

LOCTITE:
 RED 277

TORQUE:
 110±5 IN.LB.

TORQUE:
 75±5 IN.LB.

812-06-034-KIT
 Bearing Asm: [Ø1.070 Bore, 1.125-18 UNEF-2B, 0.975 TLG]

VALVING ASSEMBLY

LOCTITE:
 BLUE 242

TORQUE:
 35±2 FT.LB.

BODY

234-00-099
 Ring, Preload Collar [1.250-24 ID X 1.990 OD X .400 TLG]

804-12-008-KIT
 Body Cap Assy: Piggyback, 2011 VAN RC [1.070 Bore, Ø .500 Shaft]