

4

3

2

1

Topcap and Shaft Press-fit sub-assembly
(Not available outside of 820-05-415-KIT Topcap Assembly)

029-08-178
Seals: O-Ring [30.0mm X 1.5mm CS]
Metric, N-70, Static

229-10-700
Shaft, HSC Grip F-S [3.897 TLG]

210-03-280
Damping Adjust Part: Needle, LSC, Grip F-S, 36 180

029-08-068
Seals: O-Ring [3.0MM ID x 1.5MM CS]
Metric, N-70, Static

210-24-245
Damping Adj Part: Coupler, LSC, Grip2

038-01-073
Retaining Ring: Wire
[.280 OD X .024 CS] SS

241-02-101
Fastener, Custom (Metric):
Bolt Piston Comp Grip2

039-00-398
Spring, Comp Check, Grip2

045-00-151
Valve: Metric [18.50mm OD X 5.55mm ID
X 0.25mm THK] Custom, Check

029-08-188
Seals: O-Ring [17mm ID X 1.5mm CS]
N-90, Static

222-01-295
Piston Damping Comp 20.0 Bore

820-03-530-KIT
2019 Grip2 Compression Valving

029-08-060
Seals: O-Ring [6.0mm ID x
1.5mm CS] Metric, N-70, Static

241-02-115
Fastener Custom: Pin, Grip2

210-24-241
Damping Adj Part: Valve Loader, HSC, Grip2

029-03-011
Seals: O-Ring [(-011) .070 C.S. X .301 ID]
Standard, N-70, Static

223-00-049
Piston Floating: IFP, Grip2

029-08-196
Seals: O-Ring [16.0mm ID X
2.0mm CS] Metric, N-70, Dynamic

231-00-026
Sleeve: Isolator, Spring, OD, Grip

039-00-378
Spring, Piston, Floating, Grip 160

PROPRIETARY
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

SIZE	DWG. NO.	REV.
C	820-05-415-KIT	B
PLOT SCALE	1.5:1	SHEET

4

3

2

1