

4

3

2

1

D

D

C

C

B

B

A

A

038-01-073
Retaining Ring: Wire [.280 OD X .024 CS] SS

210-22-920
Compression Adjust Coupler, F-S, FIT4

029-08-068
Seals: O-Ring [3.0MM ID x 1.5MM CS] Metric, N-70, Static

TOPCAP ASSEMBLIES:
820-05-549-KIT: 2019 36 FIT4 F-S Topcap Assy, SPD-PED, Remote, U-Cup, 2 Position, Push-Lock, E-Bike Tune
820-05-551-KIT: 2019 36 FIT4 F-S Topcap Assy, SPD-PED, Remote, U-Cup, 3 Position, E-Bike Tune

TORQUE:
55±5 IN.LB.

TORQUE:
55±5 IN.LB.

207-11-108
(T) Pressure Tube, 15.5 Bore, 180 Max Travel, FIT4

820-03-597-KIT
2019 34 FIT4 Damper Shaft Assy, E-Bike Tune

039-00-243
Spring: Detent [.138 TLG X .087 OD X 48 lb/in] SS

010-01-012
Air Valve Parts: Ball [Ø 0.1094] E52100 Grade 25 Steel, Chrome

GREASE:
THIN LAYER
OF SLICK HONEY ON BALL

COMPRESS DAMPER SHAFT 3IN BEFORE SEALING DAMPER

ASSEMBLE THESE PARTS AFTER OIL FILL

PROPRIETARY -
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

FOX FOX Factory, Inc. Ph 831-768-1100
130 Hangar Way, Watsonville, CA 95076 USA Fax 831-768-9312

TITLE **2019 36 E-Bike+ F-S FIT4 Remote Cartridge Assemblies**

SIZE DWG. NO. **C**

PLOT SCALE | .00:1 | SHEET | OF | 1

PrøE ASSEM

4

3

2

1

PrøE ASSEM