

4

3

2

1

241-00-005  
Fastener, Custom: Nut, Bottom, R\_RL\_RLC

241-01-002  
Fastener, Custom: Crush Washer, Plastic, R\_RL\_RLC

TORQUE:  
50±5 IN.LB.  
(INTO FORK CHASSIS)

IMPORTANT:  
INSPECT 100% THAT RETAINING RING  
IS FULLY INSTALLED INTO GROOVE FULL 360°

038-00-137  
Retaining Ring: Internal, Smalley HHM-38-S02, Hoopster, 302 SS

AIR SHAFT ASSEMBLIES:  
820-02-520-KIT: Air Shaft Assy, 40, 203mm, FLOAT NA 2.1  
820-02-521-KIT: Air Shaft Assy, 2019 40, 190mm, FLOAT NA 2.1

029-03-008  
O-Ring (-008) [.070 C.S. X .176 ID]

GREASE:  
THIN LAYER  
OF SLICK HONEY

APPLY GREASE AROUND PISTON, ON 10MM SHAFT BETWEEN  
BUMPER AND NEG PLATE, AND A THIN LAYER ON ENTIRE  
LENGTH OF PISTON BORE OF UPPER TUBE ID.

820-05-346-KIT  
Topcap Assy, FLOAT NA 2, 40, Black

TORQUE:  
220±5 IN.LB.  
(INTO FORK CHASSIS)

234-04-726  
Volume Spacer, FLOAT NA 2, 40

234-04-551  
(T) Spring Hardware: 2014 40 FLOAT Air Topcap, Al, Blue Ano

PROPRIETARY  
THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION  
THAT IS FOX PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE  
FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.

	<b>FOX Factory, Inc.</b>		Ph 831-768-1100
	130 Hangar Way, Watsonville, CA 95076 USA		Fax 831-768-9312
TITLE	<b>2019 40 FLOAT</b>		
	<b>Air Spring Assemblies</b>		
SIZE	DWG. NO.		
<b>C</b>			
PLOT SCALE	.00:1	SHEET 1 OF 1	

4

3

2

1