

210-22-404
Piston Bolt: Van RC Low Speed [1/4-32, .575 TLG, 3/8 hex]

234-00-230
Spring Hardware: Van RC Spring Perch [.252 ID x 0.850 OD x .080 TLG] Steel

TORQUE:
60 ± 5 IN.LB.

INSTALL LAST WITH LIGHT SEAT AND BACKOUT 1/4 - 1/2 TURN

210-03-114
Needle: DSC Adj, LSC Adj

Shaft: Van RC, Low Speed Damping Shaft

GREASE:
THIN LAYER

234-00-139
Shuttle [.850 X .429 X .050]

234-00-140
Spring Spacer [.322 X .850 X .006]

234-00-141
Spring Spacer [.322 x .850 x .008]

(039-00-073)
039-00-073
Belleville Spring: [.825 X .330 X .008]

233-00-053
Spacer: [.252 X .425 X .050]

029-03-019
O-Ring (-019) [.070 C.S. X .801 ID]


222-01-170
Piston: Van RC Resi Piston [.940 Bore, .934 OD x .251 ID x .255 TLG]

046-20-012
Valve: [.585 OD x .358 ID x .010 TH]

039-00-165
Spring: Compression [.380TLG x .412 ID x 4.3 lb/in]

GREASE:
THIN LAYER
TO HOLD BALL IN

010-01-000
Ball [Ø 0.1250] Steel



SECTION A-A

		FOX Factory, Inc. 130 Hangar Way, Watsonville, CA 95076 USA Ph 831-768-1100 Fax 831-768-9312
TITLE Damping Adj Assy: 2011 VAN RC		
SIZE DWG. NO. C	815-02-015-KIT	
PLOT SCALE 2.00:1	SHEET 1 OF 1	

PROPRIETARY - THIS DOCUMENT CONTAINS CONFIDENTIAL - PROPRIETARY INFORMATION THAT IS FOR PROPERTY. DO NOT DISCLOSE TO OR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY FOX.